



# WCFC C-152 Quiz

Review before : 2025-03-26

Quiz ID : 12833

Instructor :		Date :
Pilot :	Member # :	Score :

**Instructor :** Please note the final score (subtract 3.0 points from 100 for each wrong answer) on the checkout form and file the quiz in the Pilot Records folder.

---

1 : When flying with the Garmin G5 instrument, wearing polarizing eyewear ...

- A : is not recommended at night
- B : will reduce glare and improve the visibility of the display
- C : is entirely optional
- D : may cause the display to appear dim or blank
- E : is unnecessary unless the eyewear is polarized strictly in the vertical axis

2 : What is the rated horsepower of the engine in the WCFC 152 aircraft?

- A : 98 BHP at 2550 RPM.
- B : 100 BHP at 2550 RPM.
- C : 108 BHP at 2550 RPM
- D : 110 BHP at 2550 RPM.

3 : What are the total fuel capacity and the useable fuel capacity for the WCFC C152s?

- A : 26 gallons, 24 gallons useable.
- B : 26 gallons, 24.5 gallons useable.
- C : 39 gallons, 38 gallons useable.
- D : 39 gallons, 37.5 gallons useable.

4 : The type of oil normally (after initial break in of a new engine or cylinder) used in the C-152 is:

- A : High quality automotive multi-grade high detergent type.
- B : SAE rated SE (Severe Environment) type multi-viscosity.
- C : Aviation grade ashless dispersant (AD) of appropriate viscosity.
- D : Aviation grade "mineral" engine oil.

5 : Which engine is installed in the Cessna 152?

- A : Lycoming O-235-N2C.
- B : Lycoming O-235-L2C
- C : Lycoming OI-235-N2C.
- D : Lycoming OI-235-L2C.

6 : What is the airspeed recommended for steep turns by the manufacturer of the C152?

- A : 65 knots.
- B : 85 knots.
- C : 95 knots.
- D : 105 knots.

7 : What is the acceptable oil quantity for the C-152?

- A : Four to six gallons.
- B : Four to six pints.
- C : Four to six quarts.
- D : Four to six liters

8 : What is the best glide speed and flap configuration for the C-152?

- A : 55 KIAS and flaps up..
- B : 55 KIAS and flaps at 10 degrees.
- C : 60 KIAS and flaps up.
- D : 60 KIAS and flaps at 10 degrees.

9 : Which of the following is the proper fuel for the C-152 (with no STC)?

- A : 100
- B : 100LL
- C : Automotive low-lead
- D : Both a and b

10 : The maximum certified weight(s) for the WCFC C-152s are:

- A : Ramp 1675; takeoff 1670; landing 1670.
- B : Ramp 1680; takeoff 1670; landing 1670.
- C : Ramp 1680; takeoff 1675; landing 1675.
- D : Ramp 1675; takeoff 1675; landing 1670.

- 11 : The wing loading and the power loading of the C152 are:
- A : determined by speed
  - B : 1675 and 1670
  - C : 10.2 and 15.5
  - D : 10.5 and 15.2
- 12 : The manual priming system draws fuel from the fuel strainer and injects it where?
- A : into the carburetor
  - B : into the fuel pump
  - C : into the intake manifold
  - D : into the cylinder intake ports
  - E : into the magnetos
- 13 : According to WCFC Standard Operating Procedures and WCFC checklists, which of the following approach and landing speed combinations is recommended by the WCFC?
- A : Normal -- flaps 20; airspeed 65 KIAS.
  - B : Short Field -- flaps 20; airspeed 54 KIAS.
  - C : Soft Field -- flaps 30; airspeed 75 KIAS.
  - D : Normal, short field, and soft field techniques are all correct.
- 14 : In a C-152, the ammeter and low voltage warning light may indicate electrical power system problems. The ammeter may show a slight charge after engine start if the battery has been partially discharged by extended cranking of the starter or other electrical draw. If, however, the ammeter continues to show a significant charge (more than two needle widths) during flight, what might this indicate and what pilot action is recommended?
- A : Turn off the alternator switch, reduce the electrical load to preserve battery power, and land as soon as practical.
  - B : Ignore it. Breakers have been built into the system for shorts. It usually indicates just that items such as the landing light are on increasing electrical demand.
  - C : Attempt to recycle the over-voltage relay by turning off the radios, and then recycling the master switch.
  - D : Turn the master switch to off and land immediately.
- 15 : Maneuvering speed for the C-152 is:
- A : 104 KIAS at 1670 pounds
  - B : 98 KIAS at 1500 pounds
  - C : 93 KIAS at 1350 pounds
  - D : 96 KCAS at 1500 pounds
  - E : All of the above

16 : In the C-152, the stall warning horn sounds at what speed?

- A : At the bottom of the green arc on the airspeed indicator
- B : At the bottom of the white arc on the airspeed indicator
- C : At 0 to 5 knots before the stall.
- D : At 5 to 10 knots before the aerodynamic stall

17 : The C-152 electrical system is a:

- A : 12 volt, direct current system with a 24 volt battery.
- B : 12 volt, direct current system with a 12 volt battery.
- C : 16 volt direct current system with a 24 volt battery.
- D : 28 volt direct current system with a 24 volt battery.

18 : Spin recovery procedures in a C-152 are:

- A : Ailerons neutral, throttle , apply and hold full rudder in the direction of rotation, control wheel briskly forward, hold until rotation stops, smoothly recover from the resulting dive.
- B : Ailerons neutral, full throttle, apply and hold full rudder opposite to rotation, control wheel briskly forward, hold until rotation stops, smoothly recover from the resulting dive.
- C : Ailerons neutral, throttle idle, apply and hold full rudder opposite to rotation, control wheel briskly forward, hold until rotation stops, smoothly recover from the resulting dive.
- D : Ailerons neutral, throttle idle, apply and hold full rudder opposite to rotation, hold until rotation stops, smoothly recover from the resulting dive.

19 : What is the maximum recommended turbulent air penetration speed for the C-152?

- A : All weights 104 KIAS.
- B : All weights 104 KCAS.
- C : 1670 lbs, 104 KCAS; 1500 lbs, 98 KCAS; 1350 lbs. 93 KCAS
- D : 1670 lbs, 104 KIAS; 1500 lbs, 98 KIAS; 1350 lbs. 93 KIAS.

20 : This G5 is configured with a ...



- A : sky pointer
- B : ground pointer

21 : After starting the engine, oil pressure:

- A : Will register immediately.
- B : Should begin to register within 90 seconds.
- C : Must register within 30 seconds in the summer and 60 seconds in the winter.
- D : Must register within 60 seconds in the summer and 90 seconds in the winter.

22 : What would indicate the presence of carburetor ice in flight?

- A : A sudden increase in oil pressure.
- B : An immediate complete loss of engine power.
- C : A gradual loss of RPM.
- D : A gradual increase in oil pressure.

23 : Which of the following statements concerning the fuel system is *false*?

- A : Fuel flows by gravity from two wing tanks to a fuel shutoff valve.
- B : Fuel pressure increases when the selector is on either tank.
- C : Fuel system venting is essential to system operation.
- D : Fuel quantity is measured by two float-type fuel quantity transmitters.

24 : Which set of procedures are the proper procedures in the proper order for a balked landing (go around) in the C152?

- A : Throttle -- full; Carburetor heat -- off; Flaps -- retract to 20 degrees; Speed -- 55 KIAS; Flaps -- Retract slowly
- B : Carburetor heat -- off; Throttle -- full; Flaps -- lower to 20 degrees; Speed -- 55 KIAS; Flaps -- Retract slowly
- C : Throttle -- full; Carburetor heat -- off; Speed -- 55 KIAS; Flaps -- retract to 10 degrees; Flaps -- Retract slowly
- D : Throttle -- full; Flaps -- lower to 20 degrees; Carburetor heat -- off; Speed -- 55 KIAS; Flaps -- Retract slowly

25 : Assuming a forward center of gravity and flaps retracted, what are the two stall speeds for a C-152 under the following conditions?

- 0 degrees of bank and 60 degrees of bank

- A : 36 KIAS and 51 KIAS.
- B : 40 KIAS and 57 KIAS.
- C : 35 KIAS and 49 KIAS.
- D : 48 KIAS and 68 KIAS.

26 : The engine operation and performance is monitored by an oil pressure gauge, an oil temperature gauge, and a tachometer. The reading of the oil pressure gauge is determined by what means?

- A : voltage from a sensor conveyed to the gauge by a wire through the firewall
- B : a direct pressure oil line from the engine to the gauge
- C : a sensor in the oil filter
- D : A capacitance reading from the oil sump

27 : In club operation of our C152 airplanes, when should you lean the fuel mixture according to the manufacturer?

- A : During all operations at any altitude when operating at 75% or less power.
- B : Only when absolutely necessary it may foul the plugs.
- C : Only when established in cruise flight above 5000 feet.
- D : Only at high altitude airports.

28 : What is the landing roll for the C-152 given the following?

- Aircraft weight : 1670 lbs
- Temperature : 30 degrees Celsius
- Pressure Altitude : 1000 feet
- Wind direction : 350 degrees
- Wind speed : 12 knots
- Runway number : 31
- Runway surface : Dry Pavement
- Speed : 54 KIAS

- A : 468 feet.
- B : 520 feet.
- C : 1270 feet.
- D : 1295 feet.

29 : What is the approximate ground roll/takeoff distance over a 50 ft obstacle given the following? (Choose the nearest answer. Due to rounding variations, your calculations may differ by a few feet.)

- Aircraft weight 1670 lbs
- Temperature 30 degrees Celsius
- Pressure Altitude 1000 feet
- Wind speed 23010
- Runway number 22
- Runway surface Grass

- A : 810/1495 feet..
- B : 1013/1768 feet
- C : 911/1584 feet
- D : 911/1891 feet

30 : Given the following data, is the C-152 aircraft within maximum takeoff and landing weight and moment limits?

Item	Weight (lbs)	Moment (in-lbs)
Basic Empty Weight 4640B	1168.4	35,578.0
Fuel Full tanks	—	—
Pilot	190.0	—
Passenger	150.0	—
Baggage Area 1	15	—
Baggage Area 2	4	—

Use the data in the table above to calculate the aircraft's W&B.

- A : Weight within limits, moment within limits.
- B : Weight within limits; moment outside of limits.
- C : Weight outside limits; moment within limits.
- D : Weight outside limits; moment outside limits.